



Shown with TA-8 Steel Casing as example.



2M Jamb Glazing - Adjustable

ADJUSTABLE FRAME - BORROWED LIGHT

Borrowed Light refers to a glazed area not attached to a door. MULLIONS ARE NOT AVAILABLE FOR A-SERIES ADJUSTABLE FRAMES.

NOTE: If mullions are required, refer to Standard Frame (S-Series and C-Series) Borrowed Lights with mullions and unrestricted design options

RELATED INFORMATION

SOUND

FRAME MATERIALS	MAX DOOR SIZE	JAMB DEPTH RANGES	RATINGS
Prefinished Steel	Max. Assembly Width: 8' - 0" Max. Assembly Height: 8' - 0"	Frame Thickness: 18 gauge Jamb Depths: 3 3/4" to 9 1/8"	Not Available

All widths and heights are inside dimensions - net glass opening size.

FIRE RATING

Min. Jamb Depth: 3 3/4" — Max. Jamb Depth: 9 1/8"		GENERAL INFORMATION			
JAMB DEPTH RANGE	45, 90 MINUTE	<ol style="list-style-type: none"> All openings are approved for Positive and Neutral pressure unless otherwise noted. All ratings apply to steel stud, wood stud, or masonry construction. All ratings approved for category "A" and "B" doors with category "G" edge sealing. Timely's fire rated <i>Metal "U" Insert</i> is recommended for masonry installations. If wood subframe is used in place of <i>Metal "U" Insert</i>, it will be necessary to use fire rated drywall on both sides of wood to maintain fire rating. Aluminum casing does not affect fire rating. Wood casing on perimeter does not affect fire rating. Wood casing on perimeter with TA-8 casing on mullion does not affect fire rating. Wood casing must be applied with hot melt glue or contact adhesive on 90 minute rated frames and on all glazed openings with 45 minute or 60 minute rating. On all other fire rated frames, wood casing can be applied with nails or finish head screws on jambs and mullions. 			
Min. Jamb Depth: 3 3/4" Max. Jamb Depth: 9 1/8"	<table border="0"> <tr> <td>Width: up to 2'</td> <td>Width: over 2' and up to 3' *</td> </tr> <tr> <td>Max. Height: 8' - 0"</td> <td>Max. Height: 4' - 6"*</td> </tr> </table> <p>Visible light is 1" less in width and height</p>		Width: up to 2'	Width: over 2' and up to 3' *	Max. Height: 8' - 0"
Width: up to 2'	Width: over 2' and up to 3' *				
Max. Height: 8' - 0"	Max. Height: 4' - 6"*				

All dimensions shown are inside dimensions - net door opening size.

* For widths exceeding 24" the maximum glass area is 1296 sq. in. unless approved by local AHJ.

Distributors of Timely Frames may be approved to purchase labels and apply them to frames at their own facility. Intertek has set guidelines and a fee schedule for this program. Requirements and prices are available from Timely or Intertek.

ROUGH OPENING DIMENSIONS

WIDTH


For Borrowed lights, the rough opening width is 1 1/4" larger than the inside glass area, including any mullions. For stepped borrowed lights, the dimension is calculated separately for each step width.

ROUGH OPENING: Glass width + 2" for each mullion + 1 1/4"

HEIGHT

For Borrowed lights, the rough opening height is 1 1/4" larger than the inside glass area, including any mullions. For stepped borrowed lights, the dimension is calculated separately for each step width.

ROUGH OPENING: Glass height + 2" for each mullion + 1 1/4"



W = Net Glass Width(s) + 2" for each Mullion + 1 1/4"

H = Net Glass Height(s) + 2" for each Mullion + 1 1/4"