

OFFICE – Professional

- Uniformity of all interior doors and frames – including stairwells and double egress frames
- Economical solution without sacrificing performance or quality
- Fire rated sidelights and borrowed lights available
- Ideal for either wood stud or steel stud framing



FRAME SELECTION RECOMMENDATIONS




		Frequency	S	C	A	CK	AK	DE	P	Galvanizing Required
Common Areas	Main Entrance	H	•	•	•	•	•	•	•	H
	Secondary Entrance	M	•	•	•	•	•	•	•	H
	Corridor Offices	M	O	O	O	P	•	•	•	H
	Interior Offices	L	P	O	O	O	•	•	•	H
	Restrooms	M	P	O	O	O	•	•	•	Y
	Meeting Rooms	L	O	O	O	P	•	•	•	H
	Closet SS/PR	L	P	O	O	•	•	•	•	H
	Sidelight		•	P	•	•	•	•	•	H
	Borrowed Light		O	P	O	•	•	•	•	H
	Mechanical/Electric	L	•	O	O	P	•	•	•	H
	Stairwell	L	•	O	•	P	•	•	•	H

Frequency	Use of Frame	Galvanizing Required
H = High M = Medium L = Low	P = Preferred O = Optional • = not recommended	Y = Always H = Galvanize in Humid Climate

CLASSIC FRAME S C

S-Series (20 gage, Factory Prefinished)



General use for all interior openings.

Minimum Jamb Depth – 2 1/4"
 Maximum Jamb Depth – 5 3/8"

Fire Rating – 90 Minutes (Minimum Jamb Depth 3 3/8" for rating)

Maximum Door Weight – 500 lbs.

C-Series (18 gage, Factory Prefinished)

General use for all interior openings requiring additional strength and impact resistance of 18 gage steel.


Minimum Jamb Depth – 2 1/4"
 Maximum Jamb Depth – 13"

Fire Rating – 90 Minutes (Minimum Jamb Depth 3 3/8" for rating)

Maximum Door Weight – 500 lbs.

ADJUSTABLE FRAME A

A-Series (18 gage, electro-galvanized, Factory Prefinished)



Use for interior openings with uneven or odd sized walls requiring non-stock wall size. Adjustable jamb thickness makes this frame Ideal for remodel projects.

Minimum Jamb Depth – 3 3/4"
 Maximum Jamb Depth – 12"

Fire Rating – 90 Minutes

Maximum Door Weight – 500 lbs.



OFFICE – Professional

Accessory Hardware



- TA-10 Regular Arm Closer Reinforcement - Can be used on all Frames
- TA-12 Parallel Arm Closer Reinforcement - Classic Frames only
- TA-47 Parallel Arm Closer Reinforcement - Kerf Frames only

CASING RECOMMENDATIONS



TA-8 Steel





TA-23 Aluminum



TA-28 Aluminum




TA-28M Aluminum
 (For use on mullions only)



KERFED FRAME

CK

CK-Series (18 gage, electro-galvanized, Factory Prefinished)



Use for interior and exterior openings requiring a seal against smoke, sound, weather, and light. Kerfed stop with factory installed seal.

Minimum Jamb Depth – 4"

Maximum Jamb Depth – 8"

Fire Rating – 90 Minutes

Maximum Door Weight – 500 lbs.